

(DESIGNATIONS OF PIECES IN IMPERIAL, DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED)
(DÉSIGNATIONS DES PIÈCES EN IMPÉRIAL, DIMENSIONS EN MILLIMÈTRE SAUF INDICATION CONTRAIRE)

Technical drawing of the 1000 Series Parallel Arm, showing three views: front, top, and side.

Front View Dimensions:

- Overall width: 989 [38.93]
- Distance between arm pivots: 330 [12.99]
- Distance from pivot to base: 219 [8.63]
- Overall height: 332 [13.09]
- Base width: 1143 [45.00]
- Base length: 1207 [47.50]
- Arm angle: 20°
- Callout 1 points to the central base section.
- Callout 2 points to the arm pivot joint.

Top View Dimensions:

- Distance between arm pivots: 152 [6.00]
- Distance from pivot to base: 64 [2.50]
- Base width: 229 [9.02]
- Base length: 17 [.69]
- Callout 3 points to the base pivot joint.
- Callout 4 points to the arm pivot joint.

Side View Dimensions:

- Overall width: 127 [5.00]
- Distance between arm pivots: 6 [0.25]
- Base width: 229 [9.02]
- Base length: 17 [0.69]
- Callout 3 points to the base pivot joint.
- Callout 4 points to the arm pivot joint.

 continental		CONTINENTAL CONVEYOR MACHINE WORKS LTD. CONVOYEUR CONTINENTAL USINAGE UITEE	
THETFORD MINES, QUEBEC, CANADA NAPANEE, ONTARIO, CANADA			
<u>STANDARD</u>			
20" TROUGH TRAINING IDLER		36" BELT WIDTH	
5" ROLL		25/25mm SHAFT	
Drawing No./Dessin No.		CEMA D5 DUTY	
Format:	A BB-40220-5-36D		Revision:
			0